


康伟栅栏式PCB接线端子


产品规格书



认证	UL CE	
电气性能	UL	IEC
参考标准	300V	750V
额定电压	20A	32A
额定电流	22-12AWG	4.0mm ²
导线线径	AC2000V/1Min	
耐电压	500MΩ/DC500V	
绝缘阻抗		
机械性能		
最大锁紧扭力	1.2Nm/10.6Lb.in	
环境温度	-40℃~+105℃	
尺寸		
间距	11.0mm(.433")	
极数	2P-22P	
材质及电镀		
塑件	PA66, UL94V-0	
端子	黄铜, 1.0厚 镀锡	
螺丝	钢, M4镀锌	



订购方式:



极数	2	3	4	5	6	7	8	9	10	11	12	13	14	15
L(mm)	24.00	35.00	46.00	57.00	68.00	79.00	90.00	101.00	112.00	123.00	134.00	145.00	156.00	167.00
S(mm)	11.00	22.00	33.00	44.00	55.00	66.00	77.00	88.00	99.00	110.00	121.00	132.00	143.00	154.00
极数	16	17	18	19	20	21	22	23	24	25	26	27	28	
L(mm)	178.00	189.00	200.00	211.00	222.00	233.00	244.00	255.00	266.00	277.00	288.00			
S(mm)	165.00	176.00	187.00	198.00	209.00	220.00	231.00	242.00	253.00	264.00	275.00			

中国·康伟电子有限公司
 NAME **KV65C-B**